



SNS-Bullet-IP-C104

3.0 MP Outdoor Bullet Camera

Main Features:

120dB WDR, 3D DNR
Triple streams
On-board storage, up to 128GB
Smart Focus: Motorized VF lens (-Z)
Smart VQD
Smart Facial Detection

Feature	Specification
Image Sensor	2.54cm (1/3inch) Progressive Scan CMOS
Shutter Speed	Support
Minimum Illumination	0.01 Lux @ (F1.2, AGC ON), 0 lux with IR 0.014 Lux @ (F1.4, AGC ON), 0 lux with IR
Shutter Speed	Support
Lens	No -Z: 2.8-12mm @ F1.4, angle of view: 91.2-28.3° 8-20mm @ F1.6, angle of view: 33.2°13.8°(optional) -Z: 2.8-12mm @ F1.4, angle of view: 91.2-28.3° 8-32mm @ F1.4, angle of view: 26°8.54°(optional)
Auto-iris	DC drive
Day & Night	IR cut filter with auto switch
IR cut filter with auto switch	3D DNR
Video Compression	Video Compression
Audio Compression	G.711/G.722.1/G.726/MP2L2
Max. Resolution	2048x1536
Image Setting	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Network Storage	NAS (Support NFS,SMB/CIFS)
Operating Conditions	30- °C – 60 °C
Power Consumption	Max. 11.5 W -Z/-H: Max. 12.5W
Ingress Protection	IP66



SNS-AHD-50IB42-VF

5.0MP AHD Outdoor Weatherproof Camera

Main Features:

1/2.8" HD-CMOS
IR Bullet Varifocal Camera
5MP Resolu"on @ (2560x1920)P
2.8~12mm Varifocal Lens
42-IR LED / up to 40-50Mtr.

Feature	Specification
Image Sensor	1/2.8" HD-CMOS
Resolution	PAL/NTSC: 2560x1920P
Minimum Illumination	0.1 Lux (Color/Day) 0Lux (B/W)
Shutter Type	1/50(1/60)s~1/100,000s
Camera Pixel	5.0MP (2560x1920P)
White Balance	Auto tracking white balance
OSD Function	Optional
Lens Furnished	2.8~12mm Varifocal Lens
Lens Type	HD Lens / IR cut filter
Gain Control	Auto
3D-DNR	Auto
IR Led / IR distance	42-IR LED / up to 40-50Mtr
Video Output	AHD-BNC
Power Source	12VDC+10%
Current Drawn	550mA (Max.)
Operating Temperature	10-°C to 55+°C